



DIN 6535 HA	DIN 6535 HB	Dc	Ds	Lc	Ln	Dn	Lt	r	z
ULC4X03030SNT03	-	3,0	6	4	15	2,8	57	0,3	4
ULC4X04030SNT05	-	4,0	6	5	16	3,8	57	0,5	4
ULC4X05030SNT05	-	5,0	6	6	20	4,8	57	0,5	4
ULC4X06030SNT05	-	6,0	6	7	24	5,7	62	0,5	4
ULC4X06030SNT10	-	6,0	6	7	24	5,7	62	1,0	4
ULC4X08030SNT05	-	8,0	8	9	30	7,6	68	0,5	4
ULC4X08030SNT10	-	8,0	8	9	30	7,6	68	1,0	4
ULC4X10030SNT05	-	10,0	10	11	38	9,5	80	0,5	4
ULC4X10030SNT10	-	10,0	10	11	38	9,5	80	1,0	4
ULC4X12030SNT05	-	12,0	12	13	46	11,5	93	0,5	4
ULC4X12030SNT10	-	12,0	12	13	46	11,5	93	1,0	4



Ap [min]	Ap [max]	Ae [max]	fz
0,3*Dc	Lc	0,5*Dc	0,0140*Dc
0,3*Dc	Lc	1*Dc	0,0120*Dc
1°	5°	0,5*Dc	0,0100*Dc
-	-	-	-
-	-	-	-
0,01*Dc	0,06*Dc	Dc - (2*r)	0,0300*Dc
-	-	-	-

Vc	P1	P2	P3	H1	H2	H3	K1	K2	M1	M2	S1	S2	N1	N2	G
	-	-	-	170	150	100	-	-	-	-	-	-	-	-	-