



DIN 6535 HA	DIN 6535 HB	Dc	Ds	Lc	Ln	Dn	Lt	c	z
ULC6X06050S	-	6,0	6	18	-	-	62	0,10	6
ULC6X08050S	-	8,0	8	24	-	-	68	0,10	6
ULC6X10050S	-	10,0	10	30	-	-	80	0,10	6
ULC6X12050S	-	12,0	12	36	-	-	93	0,15	6
ULC8X16050S	-	16,0	16	48	-	-	108	0,15	8
ULC10X20050S	-	20,0	20	60	-	-	126	0,15	10



Vc	P1	P2	P3	H1	H2	H3	K1	K2	M1	M2	S1	S2	N1	N2	G	Ap [min]	Ap [max]	Ae [max]	fz
	-	-	-	220	190	160	-	-	-	-	-	-	-	-	-	0,3*Dc	Lc	0,2*Dc	0,0100*Dc
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-