



DIN 6535 HA	DIN 6535 HB	Dc	Ds	Lc	Ln	Dn	Lt	r	z
ULC2X00230N004B	-	0,2	4	0,2	0,4	0,17	50	0,10	2
ULC2X00230N006B	-	0,2	4	0,2	0,6	0,17	50	0,10	2
ULC2X00330N006B	-	0,3	4	0,3	0,6	0,27	50	0,15	2
ULC2X00330N009B	-	0,3	4	0,3	0,9	0,27	50	0,15	2
ULC2X00330N015B	-	0,3	4	0,3	1,5	0,27	50	0,15	2
ULC2X00430N015B	-	0,4	4	0,4	1,5	0,37	50	0,20	2
ULC2X00430N030B	-	0,4	4	0,4	3,0	0,37	50	0,20	2
ULC2X00430N050B	-	0,4	4	0,4	5,0	0,37	50	0,20	2
ULC2X00530N030B	-	0,5	4	0,5	3,0	0,46	50	0,25	2
ULC2X00530N050B	-	0,5	4	0,5	5,0	0,46	50	0,25	2
ULC2X00630N030B	-	0,6	4	0,6	3,0	0,56	50	0,30	2
ULC2X00630N050B	-	0,6	4	0,6	5,0	0,56	50	0,30	2
ULC2X00830N030B	-	0,8	4	0,8	3,0	0,74	50	0,40	2
ULC2X00830N050B	-	0,8	4	0,8	5,0	0,74	50	0,40	2
ULC2X01030N050B	-	1,0	4	1,0	5,0	0,94	50	0,50	2
ULC2X01030N100B	-	1,0	4	1,0	10,0	0,94	50	0,50	2
ULC2X01030N150B	-	1,0	4	1,0	15,0	0,94	50	0,50	2
ULC2X01030N200B	-	1,0	4	1,0	20,0	0,94	75	0,50	2
ULC2X01030N250B	-	1,0	4	1,0	25,0	0,94	75	0,50	2
ULC2X01530N050B	-	1,5	4	1,5	5,0	1,44	50	0,75	2
ULC2X01530N100B	-	1,5	4	1,5	10,0	1,44	50	0,75	2
ULC2X01530N150B	-	1,5	4	1,5	15,0	1,44	50	0,75	2
ULC2X01530N200B	-	1,5	4	1,5	20,0	1,44	75	0,75	2
ULC2X01530N250B	-	1,5	4	1,5	25,0	1,44	75	0,75	2
ULC2X01530N300B	-	1,5	4	1,5	30,0	1,44	75	0,75	2
ULC2X02030N050B	-	2,0	4	2,0	5,0	1,94	50	1,00	2
ULC2X02030N100B	-	2,0	4	2,0	10,0	1,94	50	1,00	2
ULC2X02030N150B	-	2,0	4	2,0	15,0	1,94	50	1,00	2
ULC2X02030N200B	-	2,0	4	2,0	20,0	1,94	75	1,00	2
ULC2X02030N300B	-	2,0	4	2,0	30,0	1,94	75	1,00	2
ULC2X02030N400B	-	2,0	4	2,0	40,0	1,94	75	1,00	2



Ap [min]	Ap [max]	Ae [max]	fz
-	-	-	-
-	-	-	-
-	-	-	-
0,02*Dc	0,5*Dc	0,5*Dc	0,0250*Dc
-	-	-	-
-	-	-	-
-	-	-	-

Vc	P1	P2	P3	H1	H2	H3	K1	K2	M1	M2	S1	S2	N1	N2	G
-	-	-	-	105	95	60	-	-	-	-	-	-	-	-	-